

EUROBATEX®



TYPE OF MATERIAL:	Black closed-cell flexible elastomeric foam (FEF)
PRODUCT RANGE:	Tubes in pipe sections (also in self-adhesive version) and coils with thicknesses from 6 mm to 60 mm and diameters from 6 mm to 170 mm. Flat sheets or rolls (also in self-adhesive version) with thicknesses from 6 mm to 60 mm. Tapes with a thickness of 3 mm
FIELDS OF APPLICATION:	Thermal insulation of refrigeration, air conditioning and heating & plumbing services in commercial, industrial and domestic applications
DIMENSIONAL TOLERANCES:	In accordance with the European Standard EN 14304
ENVIRONMENTAL INFORMATION:	Flexible and expanded CFC and HCFC-free rubber foam. It does not damage the ozone layer (ODP zero) and does not contribute to the greenhouse effect (GWP zero). Environmental Product Declaration: registration number EPDITALY0093, released on 21/02/2020, 5 years validity, UNCPC code 3623
ADDITIONAL INFORMATION:	Self-adhesive material: acrylate based adhesive coating reinforced with mesh structure. Protection liner made of polyolefin or paper foil. Traces of silicon can be found on the foil protecting the self-adhesive coating
STORAGE CONDITIONS/SHELF LIFE:	Store the material in a dry and clean environment at a temperature between 0 °C and 35 °C and a RH between 50% and 70%. Do not expose the material to heat or direct sunlight when stored. Self-adhesive products should not be kept in storage for more than one year

PHYSICAL PROPERTIES	RESULT OBTAINED		TEST METHOD
OPERATING TEMPERATURE RANGE*	+110 °C - 45 °C (-200 °C)*		EN 14706 / EN 14707
THERMAL CONDUCTIVITY	At a mean temperature of 0 °C	Tubes thk. ≤25 mm: $\lambda \leq 0,033$ W/m-K Tubes thk. >25 mm: $\lambda \leq 0,035$ W/m-K Sheets thk. ≤32 mm: $\lambda \leq 0,033$ W/m-K Sheets thk. >32 mm: $\lambda \leq 0,034$ W/m-K Tapes: $\lambda \leq 0,033$ W/m-K	EN 12667 / EN ISO 8497
	At a mean temperature of +40 °C	Tubes thk. ≤25 mm: $\lambda \leq 0,037$ W/m-K Tubes thk. >25 mm: $\lambda \leq 0,039$ W/m-K Sheets thk. ≤32 mm: $\lambda \leq 0,037$ W/m-K Sheets thk. >32 mm: $\lambda \leq 0,038$ W/m-K Tapes: $\lambda \leq 0,037$ W/m-K	
WATER VAPOUR DIFFUSION RESISTANCE FACTOR	Tubes thk. ≤19 mm: Sheets thk. ≤25 mm: Tapes: Tubes thk. ≥25 mm: Sheets thk. ≥30 mm:	$\mu \geq 10000$ $\mu \geq 10000$ $\mu \geq 10000$ $\mu \geq 7000$ $\mu \geq 7000$	EN 13469 / EN 12086
WATER ABSORPTION	<0,1 kg/m ²		EN 13472 / EN 1609
FIRE PERFORMANCE	European Standard Euroclass	Tubes: B _s -s2,d0 Sheets: B-s3,d0 Sheets 60 mm: E Tapes: B-s2,d0	EN 13501-1
	FM Approval	FM Approved Class 4924 Product Type: Pipe and Duct insulation	Test Procedure Class Number 4924 UCB Standard No. 26-3
	USA, Canada	UL Approved Flame Class V-0 Flame Class V-0, HF-1 - thk. 3 mm	UL 94 UL 746 A - UL 746 B
	Shipyards (MED)	Meets test requirements	IMO Res. MSC.307(88); IMO MSC/Circ. 1004 (Directive MED 2014/90/UE Modules B and D)
	Swiss Reaction to Fire group	Tubes: RF2 Sheets: RF2 (cr)	VKF Directive 13-15
ANTIMICROBIAL BEHAVIOUR	No fungal and bacterial growth detected		A.A.T.C.C. Test Method 30 ISO 22196
CORROSION RISK	Meets test requirements		EN 13468

*NB: for application at temperatures lower than -45 °C, please contact our technical department.
For self-adhesive sheets and tapes, the maximum operating temperature is +90 °C. For applications at higher temperatures please contact our technical department.

System 1 CE Marking in accordance with the European Standard EN 14304.
Certification of Constancy of Performance issued by CSI S.p.A. - Bollate IT-20021.

The product meets the requirements for the achievement of the Eco-Bau classification.
For outside uses Eurobatex should be protected with Union Covering or Vec elastomeric paint.
All the normatives quoted in this document are updated to the latest issued versions.
Ultra-Fresh is a registered trademark of Thomson Research Associates, Inc.
Union Foam S.p.A. reserves the right to modify any information at any time without prior notice.